

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 February 2005 (17.02.2005)


PCT

(10) International Publication Number
WO 2005/014226 A1

- (51) International Patent Classification⁷: B24B 31/02
- (21) International Application Number:
PCT/US2003/021218
- (22) International Filing Date: 7 July 2003 (07.07.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (71) Applicant (for all designated States except US): MIKRO-NITE TECHNOLOGIES GROUP, INC [US/US]; 511 Washington Avenue, Carlstad, NJ 07072 (US).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): HOFFMAN, Steve, E. [US/US]; 6 Maple Strett, Englewood Cliffs, NJ 07632 (US).
- (74) Agent: CANNUSCIO, Robert, E.; Drinker Biddle & Reath LLP, One Logan Square, 18th and Cherry Streets, Philadelphia, PA 19103-6996 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:
— with international search report

[Continued on next page]

(54) Title: HIGH SPEED VERTICAL PROCESSOR



(57) Abstract: A vertical processor (10) for processing parts by subjecting the parts to rotational and centrifugal motion with abrasive media. The processor includes an outer drum (32), and a plurality of inner containers (34) positioned within the outer drum. The inner containers are driven into engagement with the inner surface of the outer drum by centrifugal motion. Each container has an open top. A drive system centrifugally drives the inner containers within the outer drum. A lid (62) is removably engaged with each container for closing the container. A lifting mechanism is attached to each lid for lifting the lids off of the container.

WO 2005/014226 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.